

AGME RA RADIAL RIVETING MACHINES

MODEL	RA-6	RA-12	RA-14	RA-16	RA-18	RA-20
Max. final diameter in 400 N/mm² steel	6 mm	12 mm	14 mm	16 mm	18 mm	20 mm
Adjustable riveting stroke	5-40 mm	5-40 mm	5-50 mm	5-50 mm	5-50 mm	5-50 mm
Max. air pressure	6 bars	6 bars	6 bars	-	6 bars	-
Max. hydraulic force	-	-	-	40 bars	-	65 bars
Axial force	475 daN	1.265 daN	1.880 daN	2.500 daN	3.240 daN	4.000 daN
Adjustable riveting time	0-5 sec.	0-5 sec	0-5 sec	0-5 sec	0-5 sec	0-5 sec
Power circuit	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz
Installed power	0,4 kW	0,7 kW	1,6 kW	2,8 kW	1,6 kW	2,8 kW
Control circuit	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC
Two hand safety control	Included	Included	Included	Included	Included	Included
Operation control in 6 languages	Included	Included	Included	Included	Included	Included
Parts counters	Included	Included	Included	Included	Included	Included
Stroke centesimal adjustment	Included	Included	Included	Included	Included	Included
Weight	162 Kg	173 Kg	278 KG	305 Kg	315 Kg	310 Kg

- The RA-4 and RA-30 riveting machines are built on customer's request

