

## AGME RADIAL RIVETING MACHINES

MODEL	RR-4	RR-6	RR-12	RR-14	RR-16	RR-18	RR-20	RR-30
<b>Maximum head diameter to Obtain in 40 daN/mm<sup>2</sup> steel</b>	4 mm	6 mm	12 mm	14 mm	16 mm	18 mm	20 mm	30 mm
<b>Adjustable riveting course</b>	5-30 mm	5-40 mm	5-40 mm	5-50 mm	5-50 mm	5-50 mm	5-50 mm	10-100 mm
<b>Air pressure</b>	6 bars	6 bars	6 bars	6 bars	-	6 bars	-	-
<b>Oil pressure</b>	-	-	-	-	40 bars	-	65 bars	65 bars
<b>Adjustable riveting time</b>	0-3 sec.	0-5 sec.	0-5 sec	0-5 sec	0-5 sec	0-5 sec	0-5 sec	0-5 sec
<b>Power circuit</b>	230V or 400V 50 Hz	230V or 400V 50 Hz	230V or 400V 50 Hz	230V or 400V 50 Hz	230V or 400V 50 Hz	230V or 400V 50 Hz	230V or 400V 50 Hz	230V or 400V 50 Hz
<b>Installed capacity</b>	0,3 Kw	0,4 kw	0,7 Kw.	1,7 Kw	3,2 Kw	1,7 Kw	3,2 Kw	4,6 Kw
<b>Control circuit</b>	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC
<b>Two hand control</b>	Included	Included	Included	Included	Included	Included	Included	Included
<b>Operating dialogue 4 languages</b>	-	Included	Included	Included	Included	Included	Included	Included
<b>Parts counter</b>	Included	Included	Included	Included	Included	Included	Included	Included
<b>Centesimal course adjustment</b>	Included	Included	Included	Included	Included	Included	Included	Included
<b>Weight</b>	39 Kg	102 Kg	168 Kg	273 KG	299 Kg	310 Kg	445 Kg	720 Kg

